DEWALT®

FAST MOVERS CATALOGUE

GUARANTEED TOUGH.®

www.DEWALT.ae

TOOL FEATURES

The icons under each tool indicate the product features used throughout this catalogue

CORDLESS MODELS ONLY:

Battery capacity in Amp Hours (Ah)

1.3 AH | 1.5 AH | 2.0 AH | 3.0 AH | 4.0 AH | 5.0 AH | 6.0 AH | 9.0 AH | 12.0 AH | 15.0 AH | BARE

Number of batteries supplied

1 | 2 | 3

ALL MODELS:

TWO MODE
For rotary and hammer drilling

THREE MODE
For rotary, hammer drilling and chiselling

DRILL DRIVER
For drilling and screwing

TWO OR THREE SPEED SELECTOR
Tools are available with multiple speeds for greater control in a variety of applications

FORWARD AND REVERSE
Forward and reverse action for screwdriving applications

CONSTANT SPEED
A constant speed is maintained under operational load

ELECTRONIC VARIABLE SPEED CONTROL
Speed can be adjusted from low to high giving greater control in each application

IMPACT MECHANISM
Uses rotary impacts to generate extremely high torque for fastening

SOFT START
Electronic soft start to limit start-up current and reduce kick reaction which could misalign the accessory

CLUTCH
Mechanical or Electronic Clutch reduces the kickback reaction in the event of a pinch or stall protecting the operator as well the tool against overload

NO VOLT RELEASE SWITCH
Prevents the unit from starting unintentionally when locked on. Switch must be consciously reset before power is delivered

E-BRAKE
Electronic Brake stops the wheel quickly when the trigger is disengaged

ANTI-ROTATION SYSTEM
Detects a loss of tool control and reacts by instantly cutting the power. The best safety system for the operator

BRUSH / SERVICE INDICATOR
Service light in the tool handle indicates when the brushes require changing or when service is required

LOW VIBRATION SIDE HANDLE
Low-vibration side handle with a damped mechanism ro reduce hand-arm vibration level

SUSPENDED HANDLES
Suspended handles dramatically reduce vibration, increasing productivity and end-user comfort.

ANTI-VIBRATION FLOATING HANDLE
The whole handle is completely dampened from top to bottom reducing the vibration increasing confort and productivity

ANTI-MASS SYSTEM
Counter-balance system helps reduce vibration levels

2-POSITION KEYLESS BLADE CLAMP
Allows quick blade change into 2 different positions for higher flexibility

3-POSITION KEYLESS SHOE
Length of the shoe can be adjusted to maximise blade life

4-POSITION KEYLESS BLADE CLAMP
Allows quick blade change into 4 different positions bringing flush cutting and versatility

PENDULUM BLADE ACTION
Adjustable pendulum blade action provides improved cutting performance in comparison to a conventional blade action

HOOK & LOOP
Hook & Loop bases allow easy attachment of sand paper

PALM GRIP
Tool designed for single-handed operation

PLUNGE ACTION
Parallel plunge action on routers for accuracy and cut finish or plunge mechanism for circular saws

GUIDE RAIL COMPATABLE
Tool can be used with **DEWALT** guide rail system

CROSS CUT POSITIONING SYSTEM
Shadow line cut indicator provides fast accurate alignment of the blade while illuminating the work piece for increased productivity. No adjustment required

TOOL FREE ADJUSTMENT
The accessory in use, guard or shoe of the tool can be changed or adjusted without the need of a screwdriver, key or spanner

KEYLESS CHUCK
Drills provided with keyless chuck for quick change of accessories

QUICK CHANGE CHUCK
Ideal solution to change easily between SDS and 3 jaw chuck systems

1/2 OR 3/4 ANVIL
Tool holder dimensions for Impact wrenches

6.35 HEX
Tool holder dimensions for Impact drivers and screwdrivers

SPINDLE LOCK
Spindle is locked by pushing a button allowing quick and easy change of accessories

LED
Tool is provided with LED light

AIRLOCK SYSTEM
Tool provided with quick connection system when connected to a Dust Extractor

DUST EJECTION SYSTEM
Rejects the majority of dust sucked into a grinder leaving clean air only to pass over the motor, resulting in increased durability

DUST EXTRACTION SYSTEM
Dust Extraction into either a dust bag on the tool or through an attachment to a dust extraction unit

CORDED/CORDLESS
Tool can be powered by main electricity sourceor by **DEWALT** batteries

NO GAS REQUIRED
Cordless tool using battery power instead of gas

TOOL CONNECT SYSTEM
Bluetooth technology on the tool that allow the user to connect it to the **DEWALT TOOL CONNECT APP**

WIRELESS TOOL CONTROL
The tool is equiped with wireless connection system that can be paired with dust extractor for wireless activation

CARRYING CASE
Tool Supplied with heavy duty carrying case

TSTAK CASE
Tool Supplied with heavy duty **TSTAK** carrying case (part of **DEWALT** stackable storage system)

CONTENTS

HAMMERS & CORING MACHINES	**4**
22MM 3 MODE SDS-PLUS® HAMMER	4
26MM 3 MODE SDS-PLUS® HAMMER	4
26MM 3 MODE SDS-PLUS® HAMMER	4
28MM 3 MODE SDS-PLUS® HAMMER	5
18V LI-ION BRUSHESS 26MM 3 MODE SDS-PLUS® HAMMER	5
18V LI-ION BRUSHESS 24MM 3 MODE SDS-PLUS® HAMMER	5
18V XR 5 AH ULTRA COMPACT 20MM SDS-PLUS HAMMER	6
5 KG SDS-MAX® CHIPPING HAMMER	6
40MM SDS-MAX® COMBINATION HAMMER	6
48MM SDS-MAX® COMBINATION HAMMER	7
45 MM SDS-MAX® COMBINATION HAMMER	7
8 KG SDS-MAX® CHIPPING HAMMER	7
10 KG SDS-MAX® DEMOLITION HAMMER	8
10 KG SDS-MAX CHIPPING HAMMER	8
12 KG SDS-MAX® DEMOLITION HAMMER	8
9 KG SDS-MAX® DEMOLITION HAMMER	9
12 KG SDS MAX INLINE CHIPPING HAMMER	9
AC 16 KG HEX DEMO HAMMER	9
DRILLING & FASTENING TOOLS	**10**
12V LI-ION CORDLESS COMPACT DRILL DRIVER	10
701W 10MM ROTARY DRILL	10
1300W 2 SPEED DRY DIAMOND DRILL	10
550W 10MM ROTARY DRILL	11
750W 13MM KEYED PERCUSSION DRILL	11
1200W 2 SPEED MAGNETIC DRILL PRESS	11
12V LI-ION COMPACT DRILL DRIVER	12
12V LI-ION COMPACT HAMMER DRILL DRIVER	12
18V LI-ION DRILL DRIVER	12
18V LI-ION HAMMER DRILL DRIVER	13
18V LI-ION BRUSHLESS DRILL DRIVER	13
18V LI-ION BRUSHLESS HAMMER DRILL DRIVER	13
18V LI-ION CORDLESS BRUSHLESS COMPACT DRILL DRIVER	14
18V LI-ION BRUSHLESS COMPACT HAMMER DRILL DRIVER	14
18V XR BRUSHLESS DRILL DRIVER 2 X 5AH	14
18V XR BRUSHLESS DRILL DRIVER 2 X 5AH	15
18V LI-ION BRUSHLESS PREMIUM HAMMER DRILL DRIVER	15
540W 4.8MM DRYWALL SCREWDRIVER	15
18V LI-ION BRUSHLESS IMPACT DRIVER	16
BRUSHLESS 18V XR 1356NM IMPACT WRENCH	16
18V LI-ION BRUSHLESS COLLATED DRYWALL SCREWDRIVER	16
BRUSHLESS 18V XR 406NM IMPACT WRENCH 1/2"	17
18V XR BRUSHLESS 1/2" 813NM IMPACT WRENCH	17
18V LI-ION BRUSHLESS CONCRETE NAILER	17
GRINDERS	**18**
100MM 800W ANGLE GRINDER	18
115MM 730W ANGLE GRINDER	18
115MM 950W ANGLE GRINDER	18
115MM 730W ANGLE GRINDER	19
115MM 900W ANGLE GRINDER	19
115MM 1200W ANGLE GRINDER	19
125MM 1500W ANGLE GRINDER	20
230MM 2200W ANGLE GRINDER	20
450W 6MM DIE GRINDER	20
125MM 1200W ANGLE GRINDER	21
180MM 2200W ANGLE GRINDER	21
18V LI-ION BRUSHLESS ANGLE GRINDER	21
SAWS	**22**
2300W 355MM CHOP SAW	22
1100W RECIPROCATING SAW	22
HIGH PERFORMANCE JIGSAW	23
701W TOP HANDLE JIGSAW	23
1500W 190MM CIRCULAR SAW	23
250MM 1650W MITRE SAW	24
305MM 1675W SLIDE MITRE SAW	24
SANDERS & POLISHERS	**25**
280W 1/4 SHEET ORBITAL SANDER	25
280W 125MM RANDOM ORBIT SANDER	25
1250W 150-180MM POLISHER	25
ROUTERS & CORDLESS BLOWERS	**26**
2300W 12MM (½") PLUNGE ROUTER	26
800W VARIABLE SPEED BLOWER	26
18V LI-ION CORDLESS COMPACT JOBSITE BLOWER	26
HEAT GUNS & DUST EXTRACTION	**27**
1800W STANDARD HEATGUN	27
2000W DIGITAL LED HEATGUN	27
38L CONSTRUCTION DUST EXTRACTOR M CLASS	27
POWERSTACK RANGE	**28**
18V XR 3 SPEED COMPACT IMPACT DRIVER IN TSTAK	30
18V XR BRUSHLESS 1/2" COMPACT IMPACT WRENCH	30
18V POWERSTACK COMPACT DRILL DRIVER KIT	30
18V POWERSTACK COMPACT HAMMER DRILL DRIVER KIT	31
18V 5AH POWERSTACK STARTER KIT	31
18V BRUSHLESS IMPACT WRENCH	31
18V XR 1/2" COMPACT IMPACT WRENCH	32
18V XR 1/2" COMPACT HT WRENCH	32
18V XR BRUSHLESS DRILL DRIVER	32
18V XR BRUSHLESS HAMMER DRILL DRIVER	33
18V XR BRUSHLESS 125MM GRINDER	33
18V XR GRINDER	33
18V XR SDS PLUS 2 X 5AH POWERSTACK	34
18V XR PREMIUM RECIP 2 X 5AH POWERSTACK	34
18V XR CIRC SAW 2 X 5AH POWERSTACK	34

22MM 3 MODE SDS-PLUS® HAMMER

D25033C

Max Drilling Capacity	Wood 30 mm/ Metal 13mm/ Concrete 22mm/ Core Bit 50 mm
Power Output	590W
Max Chuck Size	13 mm
No Load Speed	0-1550
Blows Per Minute	0-5680 bpm
Impact Rate	2.0 Joules EPTA
Mode Select	3
Weight	2.0 Kg
Length x Height	330 x 210 mm
Vibration Level	13.6 m/s²

26MM 3 MODE SDS-PLUS® HAMMER

D25133K

Power Input	800W
Max. Impact Energy	2.8 J
Impact Energy (EPTA 05/2009)	2.6 J
No Load Speed	0-1500 rpm
Blows Per Minute	0-5500 bpm
Optimum Drilling Capacity [Concrete]	4-14 mm
Max. Drilling Capacity [Concrete]	26 mm
Max. Drilling Capacity [Core bit/Wood/Metal]	50/30/13 mm
Operation Mode	Hammering/Rotation/ Hammering with rotation
Weight	2.6 kg
Length x Height	335 x 210 mm
Vibration Level	15.4 m/s²

26MM 3 MODE SDS-PLUS® HAMMER - WITH QUICK CHANGE CHUCK

D25134K

Power Input	800W
Max. Impact Energy	3.0 J
Impact Energy (EPTA 05/2009)	2.8 J
No Load Speed	0-1500 rpm
Blows Per Minute	0-5540 bpm
Optimum Drilling Capacity [Concrete]	4-16 mm
Max. Drilling Capacity [Concrete]	26 mm
Max. Drilling Capacity [Core bit/Wood/Metal]	65/30/13 mm
Operation Mode	Hammering/Rotation/ Hammering with rotation
Weight	3.0 kg
Length x Height	355 x 210 mm
Vibration Level	15.7 m/s²

28MM 3 MODE SDS-PLUS® HAMMER - WITH QUICK CHANGE CHUCK

D25144K

Power Input	900W
Max. Impact Energy	3.2 J
Impact Energy (EPTA 05/2009)	3.0 J
No Load Speed	0-1450 rpm
Blows Per Minute	0-5450 bpm
Optimum Drilling Capacity [Concrete]	4-18 mm
Max. Drilling Capacity [Concrete]	28 mm
Max. Drilling Capacity [Core bit/Wood/Metal]	65/30/13 mm
Operation Mode	Hammering/Rotation/ Hammering with rotation
Weight	3.1 kg
Length x Height	360 x 210 mm
Vibration Level	14.9 m/s²

18V LI-ION BRUSHESS 26MM 3 MODE SDS-PLUS® HAMMER

DCH133M1

Voltage	18V
Battery Chemistry	Li-Ion
Tool Holder	SDS-Plus
Max. Impact Energy	2.8 J
Impact Energy (EPTA 05/2009)	2.6 J
No Load Speed	0-1500 rpm
Blows Per Minute	0-5500 bpm
Optimum Drilling Capacity [Concrete]	4-14 mm
Max. Drilling Capacity [Concrete/Wood/Metal]	26/30/13 mm
Chipping Mode	Yes
Weight	2.9 kg
Length x Height	383 x 161 mm
Vibration Level	14.5 m/s²

18V LI-ION BRUSHESS 24MM 3 MODE SDS-PLUS® HAMMER

DCH273P2

Voltage	18V
Battery Chemistry	Li-Ion
Battery Capacity	5.0 Ah
Tool Holder	SDS-Plus
Max. Impact Energy	2.4 J
Impact Energy (EPTA 05/2009)	2.1 J
No Load Speed	0-1100 rpm
Blows Per Minute	0-4600 bpm
Optimum Drilling Capacity [Concrete]	4-12 mm
Max. Drilling Capacity [Concrete/Wood/Metal]	24/26/13 mm
Chipping Mode	Yes
Weight	3.1 kg
Length x Height	301 x 202 mm
Vibration Level	6.6 m/s²

18V XR 5 AH ULTRA COMPACT SDS-PLUS HAMMER

PERFORM PROTECT | 18V XR BRUSHLESS

DCH172P2

Voltage	18V
Battery Capacity	5 Ah
No Load Speed	0-1060 rpm
Blows Per Minute	0-4980 bpm
Impact Rate	1.4 Joules EPTA
Mode Select	3
Weight	2.4 kg (Including Battery)
Max Drilling Capacity	20 mm

5 KG SDS-MAX® CHIPPING HAMMER

D25810K

Power Output	1050W
Max. Impact Energy	8.5 J
Impact Energy (EPTA 05/2009)	7.1 J
Blows Per Minute	3150 bpm
Chisel Positions	18
Weight	5.6 kg
Length x Height	462 mm x 263 mm
Vibration Level	8.5 m/s^2

40MM SDS-MAX® COMBINATION HAMMER

D25481K

Power Input	1050W
Max. Impact Energy	7.3 J
Impact Energy (EPTA 05/2009)	6.1 J
No Load Speed	540 rpm
Blows Per Minute	3150 bpm
Optimum Drilling Capacity [Concrete]	16-30 mm
Max. Drilling Capacity [Concrete]	40 mm
Max. Drilling Capacity [Core bit]	100 mm
Operation Mode	Hammering/Rotation/ Hammering with rotation
Weight	5.9 kg
Length x Height	453 x 263 mm
Vibration Level	9.4 m/s^2

48MM SDS-MAX® COMBINATION HAMMER - WITH ANTI ROTATION SYSTEM

PERFORM PROTECT

D25733K

Power Output	1600W
Max. Impact Energy	15.7 J
Impact Energy (EPTA 05/2009)	13.3 J
No Load Speed	177-355 rpm
Blows Per Minute	1350-2707 bpm
Optimum Drilling Capacity [Concrete]	24-42 mm
Max. Drilling Capacity [Concrete]	48 mm
Max. Drilling Capacity [Core bit]	125 mm
Operation Mode	Hammering/Hammering with rotation
Weight	9.2 kg
Length x Height	544 x 292 mm
Vibration Level	9.6 m/s^2

45 MM SDS-MAX® COMBINATION HAMMER

PERFORM PROTECT

D25614K

Max Drilling Capacity (Core Bit)	115 mm
Optimum Drilling Capacity (Concrete)	20- 35 mm
Voltage	220V
Max Drilling Capacity	Concrete 45 mm
Power Input	1350W
No Load Speed	190-380 rpm
Blows Per Minute	1450-2900 bpm
Impact Rate	10.5 Joules EPTA
Mode Select	3
Operation Mode	Hammering/Rotation/ Hammering with rotation
Weight	6.8 kg
Length x Height	455 x 265 mm
Vibration Level	9.6 m/s^2

8 KG SDS-MAX® CHIPPING HAMMER

PERFORM PROTECT

D25872K

Power Output	1600W
Max. Impact Energy	15.7 J
Impact Energy (EPTA 05/2009)	13.3 J
Blows Per Minute	1350-2708 bpm
Chisel Positions	12
Weight	8.6 kg
Length x Height	544 mm x 292 mm
Vibration Level	9.7 m/s^2

10 KG SDS-MAX® DEMOLITION HAMMER

D25899K

Power Output	1500W
Max. Impact Energy	19.5 J
Impact Energy (EPTA 05/2009)	17.9 J
Blows Per Minute	2040 bpm
Chisel Positions	12
Weight	9.5 kg
Length x Height	650 mm x 250 mm
Vibration Level	12.0 m/s²

10 KG SDS-MAX CHIPPING HAMMER

D25881K

No Load Speed	1060-2160 rpm
Impact Rate	17.5 Joules EPTA
Length	559 mm
Vibration Value	14.9 M/S^2
Chisel Positions	12
Weight	10.4 kg

12 KG SDS-MAX® DEMOLITION HAMMER

PERFORM PROTECT

D25951K

Power Output	1600W
Max. Impact Energy	30.1 J
Impact Energy (EPTA 05/2009)	24 J
Blows Per Minute	1621 bpm
Chisel Positions	12
Weight	12 kg
Length x Height	750 mm x 250 mm
Vibration Level	8.8 m/s²

9 KG SDS-MAX® DEMOLITION HAMMER

PERFORM PROTECT

D25892K

Power Output	1700W
Max. Impact Energy	22.7 J
Impact Energy (EPTA 05/2009)	19.4 J
Blows Per Minute	1105-2211 bpm
Chisel Positions	12
Weight	9 kg
Length x Height	591 mm x 292 mm
Vibration Level	13.5 m/s²

12 KG SDS MAX INLINE CHIPPING HAMMER

PERFORM PROTECT

D25911K

Power	1700W
Max Impact Energy	27 Joules EPTA
Chisel Positions	12
Length	765 mm
Vibration Value	6.0 M/S^2
No Load Speed	1350 - 1620 bpm
Weight	12.7 kg

AC 16 KG HEX DEMO HAMMER

PERFORM PROTECT

D25966K

Power	1800W
Chisel Positions	1
Vibration Value	6.8 M/S^2
Max Impact Energy	41 Joules EPTA
Length	770 mm
No Load Speed	1080 bpm
Weight	16 kg

12V LI-ION CORDLESS COMPACT DRILL DRIVER

12V XR

DCD700C2

Voltage	12V
Battery Chemistry	Li-Ion
Battery Capacity	1.3 Ah
Max. Torque (Soft / Hard)	15 / 24 Nm
No Load Speed	0-400/1500 rpm
Chuck Capacity	1-10 mm
Max. Drilling Capacity [Wood / Metal]	20 / 10 mm
Weight	1.1 kg
Length x Height	185 x 195 mm

1.3 AH · Electronic · LED · 2

701W 10MM ROTARY DRILL

DWD112

Power Input	701W
Chuck Capacity	10 mm
No Load Speed	0-2500 rpm
Max. Torque	10.9 Nm
Max. Drilling Capacity [Wood]	25 mm
Max. Drilling Capacity [Metal]	10 mm
Spindle Thread	1/2" x 20 U.N.F
Weight	1.8 kg
Length x Height	230 x 190 mm

Electronic

1300W 2 SPEED DRY DIAMOND DRILL

PERFORM PROTECT

D21570K

Power Input	1300W
Spindle Thread	1/2" X 20 U.N.F
No Load Speed	0-1250 / 0-3500 rpm
Max. Drilling Capacity [Concrete]	22 mm
Max. Drilling Capacity [Masonry]	127 mm
Collar Diameter	43 mm
Weight	3 kg
Length x Height	380 x 215 mm
Chuck Capacity	16 mm
Coring Capacity	Speed 1 -127 mm/ Speed 2 - 65 mm
Inclusions	Electric Overload Protection

Electronic

550W 10MM ROTARY DRILL

DWD014S

Power Input	550W
Chuck Capacity	10 mm
No Load Speed	0-2800 rpm
Max. Torque	7.9 Nm
Max. Drilling Capacity [Wood]	25 mm
Max. Drilling Capacity [Metal]	10 mm
Spindle Thread	1/2" x 20 U.N.F
Weight	1.34 kg
Length x Height	225 x 170 mm

Electronic

750W 13MM KEYED PERCUSSION DRILL

DWD024

Power Input	750W
Chuck Capacity	13 mm
No Load Speed	0-2800 rpm
Max. Torque	8.6 Nm
Blows Per Minute	47600 bpm
Max. Drilling Capacity [Wood]	25 mm
Max. Drilling Capacity [Metal]	13 mm
Max. Drilling Capacity [Concrete]	16 mm
Weight	1.82 kg
Length x Height	255 x 180 mm

Electronic

1200W 2 SPEED MAGNETIC DRILL PRESS

DWE1622K

Power Input	1200W
Speed Settings	2 speed
No Load Speed	300/450 rpm
Cutter Holder	19 mm Weldon shank (3/4")
Max. Cutting Depth with Cutters	50 mm
Max. Cutting Diameter with Cutters	50 mm
Drill Point Pressure	317 kg
Clamping Force	3800 N
Stroke Length	147 mm
Weight	14.55 kg
Magnetic Base Dimensions	180 x 84 mm
Inclusions	3/8" AW Chuck Adaptor

DRILLING & FASTENING TOOLS

12V LI-ION COMPACT DRILL DRIVER

DCD710D2

12V XR

Voltage	12V
Battery Chemistry	Li-Ion
Battery Capacity	2.0 Ah
Max. Torque (Soft / Hard)	15 / 24 Nm
No Load Speed	0-400/1500 rpm
Chuck Capacity	1-10 mm
Max. Drilling Capacity [Wood / Metal]	20 / 10 mm
Weight	1.1 kg
Length x Height	185 x 195 mm

2.0 AH · Electronic · LED · 2

12V LI-ION COMPACT HAMMER DRILL DRIVER

DCD716D2

12V XR

Voltage	12V
Battery Chemistry	Li-Ion
Battery Capacity	2.0 Ah
Max. Torque (Soft / Hard)	16 / 30 Nm
No Load Speed	0-400/1500 rpm
Beats per Minute	0-6000/22500 bpm
Chuck Capacity	1-10 mm
Max. Drilling Capacity [Wood / Metal / Masonry]	20 / 10 / 6 mm
Weight	1.18 kg
Length x Height	200 x 210 mm

2.0 AH · Electronic · LED · 2

18V LI-ION DRILL DRIVER

DCD771S2

18V XR

Voltage	18V
Battery Chemistry	Li-ion
Battery Capacity	1.5 Ah
Max. Torque (Hard)	42 Nm
Max. Torque (Soft)	24 Nm
No Load Speed	0-450/1500 rpm
Chuck Capacity	1.5-13 mm
Max. Drilling Capacity [Wood/Metal]	30/13 mm
Weight	1.65 kg
Length x Height	219 x 191 mm

1.5 AH · Electronic · LED · 2

18V LI-ION HAMMER DRILL DRIVER

DCD776S2

18V XR

Voltage	18V
Battery Chemistry	Li-Ion
Battery Capacity	1.5 Ah
Max. Torque (Hard)	42 Nm
Max. Torque (Soft)	24 Nm
No Load Speed	0-400/1500 rpm
Beats Per Minute	0-7650/25500 bpm
Chuck Capacity	1.5-13 mm
Max. Drilling Capacity [Wood/Metal/Masonry]	30/13/13 mm
Weight	1.7 kg
Length x Height	228 x 191 mm

1.5 AH · Electronic · LED · 2

18V LI-ION BRUSHLESS DRILL DRIVER

DCD777S2

18V XR BRUSHLESS

Voltage	18V
Battery Chemistry	Li-ion
Battery Capacity	1.5 Ah
Max. Torque (Hard)	65 Nm
Max. Torque (Soft)	26 Nm
No Load Speed	0-500/1750 rpm
Chuck Capacity	1.5-13 mm
Max. Drilling Capacity [Wood/Metal]	30/13 mm
Weight	1.5 kg
Length x Height	192 x 198 mm

1.5 AH · Electronic · LED · 2

18V LI-ION BRUSHLESS HAMMER DRILL DRIVER

DCD778S2

18V XR BRUSHLESS

Voltage	18V
Battery Chemistry	Li-Ion
Battery Capacity	1.5 Ah
Max. Torque (Hard)	65 Nm
Max. Torque (Soft)	26 Nm
No Load Speed	0-500/1750 rpm
Beats Per Minute	0-8500/29750 bpm
Chuck Capacity	1.5-13 mm
Max. Drilling Capacity [Wood/Metal/Masonry]	30/13/13 mm
Weight	1.55 kg
Length x Height	204 x 198 mm

1.5 AH · Electronic · LED · 2

DRILLING & FASTENING TOOLS

18V LI-ION CORDLESS BRUSHLESS COMPACT DRILL DRIVER

DCD791P2

Voltage	18V
Battery Chemistry	Li-ion
Battery Capacity	5.0 Ah
Max. Torque (Hard)	70 Nm
Max. Torque (Soft)	27 Nm
No Load Speed	0-550/2000 rpm
Chuck Capacity	1.5-13 mm
Max. Drilling Capacity [Wood/Metal]	40/13 mm
Weight	1.72 kg
Length x Height	173 x 203 mm

18V LI-ION BRUSHLESS COMPACT HAMMER DRILL DRIVER

DCD796P2

Voltage	18V
Battery Chemistry	Li-Ion
Battery Capacity	5.0 Ah
Max. Torque (Hard)	70 Nm
Max. Torque (Soft)	27 Nm
No Load Speed	0-550/2000 rpm
Beats Per Minute	0-9350/34000 bpm
Chuck Capacity	1.5-13 mm
Max. Drilling Capacity [Wood/Metal/Masonry]	40/13/13 mm
Weight	1.82 kg
Length x Height	190 x 203 mm

18V XR BRUSHLESS DRILL DRIVER 2 X 5AH

DCD800P2T

Max. Torque	90nm
Voltage	18V
Battery Capacity	5 Ah
Max Drilling Capacit	Wood 55 mm / Metal 13 mm / Masonry 13 mm
No Load Speed	0-650/0-2000
Beats Per Minute	0-34000
Chuck Capacity	13 mm
Modes	Drilling/ Screwdriving
Weight	1.28 kg

18V XR BRUSHLESS DRILL DRIVER 2 X 5AH

DCD805P2T

Max. Torque	90 Nm
Voltage	18V
Battery Capacity	5 Ah
Max Drilling Capacity	Wood 55 mm / Metal 13 mm / Masonry 13 mm
No Load Speed	0-2000 rpm
Beats Per Minute	0-34000 bpm
Modes	Hammering/ Drilling/ Screwdriving
Weight	1.34 kg

18V LI-ION BRUSHLESS PREMIUM HAMMER DRILL DRIVER

DCD996P2

Voltage	18V
Battery Chemistry	Li-Ion
Battery Capacity	5.0 Ah
Max. Torque (Hard)	95 Nm
Max. Torque (Soft)	66 Nm
No Load Speed	0-450/1300/2000 rpm
Beats Per Minute	0-8600/25500/38250 bpm
Chuck Capacity	1.5-13 mm
Max. Drilling Capacity [Wood/Metal/Masonry]	55/15/16 mm
Weight	2.2 kg
Length x Height	213 x 208 mm
Inclusions	E-Clutch

540W 4.8MM DRYWALL SCREWDRIVER

DW274KN

Power Input	540W
Max. Torque	10 Nm
No Load Speed	0-4000 rpm
Max. Screw Diameter	4.8 mm
Bit Holder	6.35 mm (Hex)
Weight	1.3 kg
Length x Height	306 x 186 mm

18V LI-ION BRUSHLESS IMPACT DRIVER

18V XR BRUSHLESS

DCF887P2

Voltage	18V
Battery Chemistry	Li-Ion
Battery Capacity	5.0 Ah
Max. Torque	205 Nm
No Load Speed	0-1000/2800/3250 rpm
Impact Rate	0 - 3800 ipm
Max. Bolt Diameter	M14
Tool Drive	6.35 mm (1/4")
Weight	1.52 kg
Length x Height	134 x 245 mm

5.0 AH · Electronic · 6.35 Hex · 2 · TSTAK

BRUSHLESS 18V XR 1356NM IMPACT WRENCH

18V XR

DCF900P2T

Breakaway Torque	1898 Nm
Fastening Torque	1396 Nm
Voltage	18V
Power Output	760W
No Load Speed	0-3200 rpm
Impact Rate	0-3200 ipm
Mode Select	4
Tool Drive	12.7 mm (1/2")
Weight	2.8 kg

5.0 AH · Electronic · 6.35 Hex · 2 · TSTAK

18V LI-ION BRUSHLESS COLLATED DRYWALL SCREWDRIVER

18V XR BRUSHLESS

DCF620P2K

Voltage	18V
Battery Chemistry	Li-Ion
Battery Capacity	5.0 Ah
Tool Drive	6.35 mm
Max. Torque	5 - 30 Nm
No Load Speed	0 - 4400 rpm
Max. Screw Length	57 mm
Weight	1.7 kg
Length x Height	380 x 233 mm

DCF6201 COLLATED MAGAZINE ATTACHMENT

Screw length suitability 25–57mm

Weight 0.36 kg

5.0 AH · Electronic · 6.35 Hex · 2 · TSTAK

BRUSHLESS 18V XR 406NM IMPACT WRENCH 1/2"

18V XR BRUSHLESS

DCF921P2T

Voltage	18V
Battery Capacity	5 Ah
Fastening Torque	406 Nm
Breakaway Torque	610 Nm
Compact Head Length	125 mm
No Load Speed	0-2500 rpm
Impact Rate	0-3550 ipm
Mode Select	4
Tool Drive	12.7 mm (1/2")
Weight	1.7 kg

4.0 AH · Electronic · 6.35 Hex · 2 · TSTAK

18V XR BRUSHLESS 1/2" 813NM IMPACT WRENCH

18V XR

DCF891P2T - WITH 2 X 18V XR 5.0AH + TSTAK

Fastening Torque	813 Nm
Max. Breakaway Torque	1084 Nm
Voltage	18V
Battery Capacity	5 Ah
No Load Speed	0-2000 rpm
Impact Rate	0-3250 ipm
Max Bolt Diameter	M16 (24 mm Socket Size)
Mode Select	4
Tool Drive	12.7 mm (1/2")
Weight	1.6 kg

5.0 AH · Electronic · 6.35 Hex · 2 · TSTAK

18V LI-ION BRUSHLESS CONCRETE NAILER

18V XR BRUSHLESS

DCN890P2

Voltage	18V
Battery Chemistry	Li-Ion
Battery Capacity	5.0 Ah
Nail Diameter	2.6 - 3.7 mm
Nail Length	13 - 57 mm
Nail Width	5.6 - 6.4 mm
Magazine Angle	15°
Magazine Capacity	Up to 30 Nails
Magazine Loading	Underneath
Operating Mode	Sequential and Rapid Cycle
Nose Included	Non magnetic / Drywall nose
Weight	4.8 kg
Length x Height	415 x 390 mm

5.0 AH · LED · NO GAS · 2

100MM 800W ANGLE GRINDER - PADDLE SWITCH

DWE4002

Power Input	800W
Disc Diameter	100 mm
Switch Type	Paddle
No Load Speed	12000 rpm
Spindle Thread	M10
Weight	1.72 kg
Length x Height	270 x 80 mm

115MM 730W ANGLE GRINDER - TOGGLE SWITCH

DWE4010T

Power Input	730W
Disc Diameter	115 mm
Switch Type	Toggle
No Load Speed	11000 rpm
Spindle Thread	M14
Weight	1.8 kg
Length x Height	270 x 80 mm

115MM 950W ANGLE GRINDER - SLIDE SWITCH

DWE4114

Power Input	950W
Disc Diameter	115 mm
Switch Type	Slide
No Load Speed	12000 rpm
Spindle Thread	M14
Weight	1.8 kg
Length x Height	270 x 80 mm

115MM 730W ANGLE GRINDER - SLIDE SWITCH

DWE4010

Power Input	730W
Disc Diameter	115 mm
Switch Type	Slide
No Load Speed	11000 rpm
Spindle Thread	M14
Weight	1.8 kg
Length x Height	270 x 80 mm

115MM 900W ANGLE GRINDER - PADDLE SWITCH

DWE4120

Power Input	900W
Disc Diameter	115 mm
Switch Type	Paddle
No Load Speed	11800 rpm
Spindle Thread	M14
Weight	2.05 kg
Length x Height	270 x 80 mm

115MM 1200W ANGLE GRINDER - PADDLE SWITCH

DWE4212

Power Input	1200W
Disc Diameter	115 mm
Switch Type	Paddle
No Load Speed	11000 rpm
Spindle Thread	M14
Weight	2.2 kg
Length x Height	285 x 80 mm

125MM 1500W ANGLE GRINDER - PADDLE SWITCH

DWE4234

Power Input	1500W
Disc Diameter	125 mm
Switch Type	Paddle
No Load Speed	11000 rpm
Spindle Thread	M14
OverLoad Protection	Yes
Weight	2.5 kg
Length x Height	285 x 80 mm

230MM 2200W ANGLE GRINDER

DWE492

Power Input	2200W
Disc Diameter	230 mm
Switch Type	Trigger
No Load Speed	6600 rpm
Spindle Thread	M14
Weight	5.2 kg
Length x Height	490 x 151 mm

450W 6MM DIE GRINDER - PADDLE SWITCH

DWE4887N

Power Input	450W
Collet Size	6 mm
Switch Type	Paddle
No Load Speed	25000 rpm
Max. Wheel Diameter	38 mm
Spindle Thread	M15
Weight	1.6 kg
Length	356 mm

125MM 1200W ANGLE GRINDER - SLIDE SWITCH

DWE4215

Power Input	1200W
Disc Diameter	125 mm
Switch Type	Slide
No Load Speed	11000 rpm
Spindle Thread	M14
Weight	2.2 kg
Length x Height	285 x 80 mm

180MM 2200W ANGLE GRINDER

DWE493

Power Input	2200W
Disc Diameter	180 mm
Switch Type	Trigger
No Load Speed	8500 rpm
Spindle Thread	M14
Weight	5.1 kg
Length x Height	484 x 112 mm

18V LI-ION BRUSHLESS ANGLE GRINDER - SLIDE SWITCH

PERFORM PROTECT 18V XR BRUSHLESS

DCG405P2

Voltage	18V
Battery Chemistry	Li-Ion
Battery Capacity	5.0 Ah
Disc Diameter	125 mm
Spindle Thread	M14
Switch Type	Slider
No Load Speed	9000 rpm
Weight	2.37 kg
Length x Height	310 x 125 mm

2300W 355MM CHOP SAW

D28730

Power Input	2300W
No Load Speed	4000 rpm
Wheel Diameter	355 mm
Max. Cutting Capacity at 90°	
[Square Profile]	120 x 120 mm
[Rectangular Profile]	115 x 130 mm
[L-Shape Profile]	135 x 135 mm
[Rounded Profile]	130 mm
Max. Cutting Capacity at 45°	
[Square Profile]	102 x 102 mm
[Rectangular Profile]	110 x 102 mm
[L-Shape Profile]	110 x 110 mm
[Rounded Profile]	115 mm
Weight	15.5 kg
Length x Height	520 x 435 mm

1100W RECIPROCATING SAW

DWE305PK

Power Input	1100W
No Load Stroke Rate	0-2800 spm
Stroke Length	29 mm
Max. Cutting Capacity [Wood]	280 mm
Max. Cutting Capacity [Steel Sections & Pipes]	100 mm
Max. Cutting Capacity [PVC]	130 mm
Weight	3.5 kg
Length x Height	435 x 178 mm

HIGH PERFORMANCE JIGSAW

DWE349

Power Output	350W
Stroke Length	20 mm
No Load Stroke Rate	500 spm - 3200 spm
Cut Capacity	Wood 85 mm / Aluminium 20 mm / Steel 10mm
Pendulum Mode	4 Positions
Tool-free Bevel Angle Set	Yes
Keyless Blade Change	Yes
Weight	2.4 kg

701W TOP HANDLE JIGSAW

DW331K

Power Input	701W
No Load Stroke Rate	0-3100 spm
Stroke Length	26 mm
Bevel Capacity	45°
Max. Depth of Cut (Wood)	130 mm
Max. Depth of Cut (Steel)	12 mm
Max. Depth of Cut (Non Ferrous Metal)	30 mm
Tool-free Bevel Angle Set	Yes
Keyless Blade Change	Yes
Weight	2.6 kg
Length x Height	250 x 210 mm

1500W 190MM CIRCULAR SAW

DWE5615

No Load Speed	5500 rpm
Power	1500W
Bore Diameter	30 mm
Blade Diameter	190 mm
Max. Cutting Capacity at 90º	68 mm
Bevel Capacity	45º
Weight	4 kg

250MM 1650W MITRE SAW

DW714

Power Input	1650W
Blade Speed	4600 rpm
Blade Diameter	250 mm
Blade Bore Diameter	30 mm
Bevel Capacity	48/0 °
Mitre Capacity [right/left]	52/47 °
Cutting Capacity at 90°/90° (W x H)	130 x 68 mm
Cutting Capacity at 90°/45° (W x H)	130 x 40 mm
Cutting Capacity at 45°/90° (W x H)	91 x 68 mm
Max. Cutting Capacity at 45°/45°	91 x 40 mm
Max. Depth of Cut [Saws]	89 mm
Weight	13.1 kg
Length x Height	600 x 425 mm

305MM 1675W SLIDE MITRE SAW - WITH VARIABLE SPEED

DWS780

Power Input	1675W
Blade Speed	1900 - 3800 rpm
Blade Diameter	305 mm
Blade Bore Diameter	30 mm
Bevel Capacity	49 °
Mitre Capacity [right/left]	60 / 50 °
Cutting Capacity at 90°/90° (W x H)	345 x 76 mm
Cutting Capacity at 90°/45° (W x H)	244 x 76 mm
Cutting Capacity at 45°/90° (W x H)	268 x 63 mm
Max. Cutting Capacity at 45°/45°	212 x 76 mm
Max. Depth of Cut [Saws]	170 mm
Weight	24.8 kg
Length x Height	770 x 396 mm

280W 1/4 SHEET ORBITAL SANDER

PERFORM PROTECT

DWE6411

Power Input	280W
Orbits Per Minute	14,000 opm
Orbit Size	1.6 mm
Paper Size	140 x 115 mm
Pad Size	108 x 115 mm
Weight	1.28 kg
Length x Height	160 x 135 mm

280W 125MM RANDOM ORBIT SANDER

PERFORM PROTECT

DWE6423

Power Input	280W
Variable Speed	Yes
Orbits Per Minute	8,000-12,000 opm
Orbit Size	2.6 mm
Paper Size	125 mm
Weight	1.28 kg
Length x Height	170 x 140 mm

1250W 150-180MM POLISHER - WITH VARIABLE SPEED

DWP849X

Power Input	1250W
No Load Speed	0–600/0–3500 rpm
Max. Backing Pad Diameter	230 mm
Recommended Pad Diameter	150 - 180 mm
Spindle Thread	M14
Weight	3.0 kg
Length x Height	480 x 135 mm

2300W 12MM (½") PLUNGE ROUTER

DWE625

Power Input	2300W
Collet Size	6mm / 8mm/ 12mm/ ¼"/ ½"
Max cutter Diameter	50mm
No- Load Speed	8000-20000 rpm
Plunge Depth	80 mm
Weight	5.1 kg

800W VARIABLE SPEED BLOWER

DWB800

Power Input	800W
Speed	0 - 16000 rpm
Air Volume	4.5 m3/min
Suction	2.5 m3/min
Weight	1.8 kg

18V LI-ION CORDLESS COMPACT JOBSITE BLOWER

18V XR

DCV100

Voltage	18V
Battery Chemistry	Li-Ion
Fan Speed	0-18,000 rpm
Air Speed	80 m/s
Speed Setting	Yes
Air Volume	2.8 m^3/min
Lock-on Switch	Yes
Suction Mode	Yes
Weight	1.3 kg
Length x Height	508 x 200 mm

BARE

1800W STANDARD HEATGUN

D26411

Power Input	1800W
Operating Temperature [Setting 1]	50 - 400 °C
Operating Temperature [Setting 2]	250 / 450 l/min
Weight	0.80 kg
Length x Height	253 x 210 mm

2000W DIGITAL LED HEATGUN

D26414

Power Input	2000W
Operating Temperature	50 - 600 °C
Air Flow	650 l/min
Weight	0.85 kg
Length x Height	265 x 210 mm

38L CONSTRUCTION DUST EXTRACTOR M CLASS

DWV905M

Max. Torque	1400W
Airflow	75 Litres Per Second
Air Pressure	250 Millibar
Extraction Classes Available	M Class
Tank Capacity	38 Litres
Weight	15 kg

18V XR POWERSTACK 5AH BATTERY

Revolutionary pouch cells deliver increased power* and work per charge**

Part of the 18V XR POWERSTACK platform and comptaible wit 18V XR tools

THE NEXT DIMENSION IN POWER™ now available in 5AH. Get 50% more power* enabling faster application speeds and increased productivity with more than 50% more work per charge** using this battery that works with all the 18V XR tools you already have. This battery provides twice the lifetime*** and features an impact-resistant, overmolded base with non-marring material.

*vs. DEWALT DCB184 battery, not in application **Usable energy vs. DEWALT DCB184 battery, not in application ***Charge cycles vs. DEWALT DCB184 battery.

Copyright ©2022 DEWALT. The following are examples of trademarks for one or more DEWALT power tools and accessories: the yellow and black color scheme; the "D"-shaped air intake grill; the array of pyramids on the handgrip; the kit box configuration; and the array of lozenge-shaped humps on the surface of the tool.

18V XR 3 SPEED COMPACT IMPACT DRIVER IN TSTAK

DCF850E2T

Voltage	18V
Battery Capacity	5 Ah
Fastening Torque	205 Nm
No Load Speed	0-1000 / 2800 / 3250 rpm
Impact Rate	0-3800 ipm
Mode Select	3
Weight	0.9 kg

18V XR BRUSHLESS 1/2" COMPACT IMPACT WRENCH

DCF921E2T - WITH 2 X 18V POWERSTACK BATTERIES + TSTAK

Max. Torque	406 Nm
Voltage	18V
No Load Speed	0 - 2500 rpm
Impact Rate	0-3550 ipm
Mode Select	4
Compact Head Length	125 mm
Weight	0.9 kg

18V POWERSTACK COMPACT DRILL DRIVER KIT

DCD800E2T

Max. Torque	90/27 Nm
Voltage	18V
No Load Speed	0-650 / 2000 rpm
Max Drilling Capacity	Wood 55 mm/ Metal 13mm
No. of Torque Settings	15
Chuck Capacity	1.5-13 mm
Weight	1.28 kg

18V POWERSTACK COMPACT HAMMER DRILL DRIVER KIT

DCD805E2T

Max. Torque	90/27 Nm
Voltage	18V
Battery Capacity	1.7 Ah
Max Drilling Capacity	Wood 55 mm / Steel 13 mm / Masonry 13 mm
No Load Speed	0-650 / 2000 rpm
Beats Per Minute	0-34000 bpm
Chuck Capacity	1.5-13 mm
Weight	1.34 kg

18V 5AH POWERSTACK STARTER KIT

DCD999H2T

Max. Torque	126.9 Nm
Voltage	18V
Max Drilling Capacity	Wood 55 mm / Metal 15 mm / Masonry 13 mm
Chuck Capacity	1.5- 13 mm
No Load Speed	0-500/ 1500/2250 rpm
Mode Select	3
Weight	1.7 kg

18V BRUSHLESS IMPACT WRENCH

DCF891H2T - WITH 2 X 5AH POWERSTACK BATTERIES

Max. Breakaway Torque	1084 Nm
Voltage	18V
No Load Speed	2000 rpm
Anvil	1/2" - Hogring
Impact Rate	3250 ipm
Mode Select	4
Weight	1.6 kg

POWERSTACK TOOL KITS

18V XR 1/2" COMPACT IMPACT WRENCH

POWER STACK

DCF900H2T - WITH 2 X 5AH POWERSTACK BATTERIES

Max Fastening Torque	1396 Nm
Max Breakaway Torque	1898 Nm
Voltage	18V
No Load Speed	2400 rpm
Anvil	1/2" Hog Ring
Impact Rate	3100 ipm
Max Bolt Diameter	M22 (34mm Socket Size)
Weight	2.8 kg

18V XR 1/2" COMPACT HT WRENCH

POWER STACK

DCF921H2T - WITH 2 X 5AH POWERSTACK BATTERIES

Max. Breakaway Torque	610 Nm
Voltage	18V
Anvil	1/2" - Hogring
No Load Speed	2500 rpm
Impact Rate	3600 ipm
Mode Select	4
Weight	1.1 kg

18V XR BRUSHLESS DRILL DRIVER

POWER STACK

DCD800H2T - WITH 2 X 5AH POWERSTACK BATTERIES

Max. Torque	90 Nm
Voltage	18V
Battery Capacity	5 Ah
Max Drilling Capacity	Wood 55 mm / Metal 13 mm
Chuck Capacity	13 mm
No Load Speed	0-650/0-2000 rpm
Mode Select	2
Weight	1.2 kg

18V XR BRUSHLESS HAMMER DRILL DRIVER

POWER STACK

DCD805H2T - WITH 2 X 5AH POWERSTACK BATTERIES

Max. Torque	90 Nm
Voltage	18V
Chuck Capacity	13 mm
Max Drilling Capacity	Wood 55 mm / Metal 13 mm / Masonry 13 mm
Battery Capacity	5 Ah
No Load Speed	0-2000 rpm
Beats Per Minute	0-34000 bpm
Mode Select	3
Weight	1.34 kg

18V XR BRUSHLESS 125MM GRINDER

POWER STACK

DCG405H2T - WITH 2 X 5AH POWERSTACK BATTERIES

Voltage	18V
Battery Capacity	5 Ah
No Load Speed	9000 rpm
Spindle Diameter	M14
Wheel Thickness	6 mm
Wheel Diameter	125 mm
Mode Select	3
Weight	2.5 kg

18V XR GRINDER

POWER STACK

DCG409H2T - WITH 2 X 5AH POWERSTACK BATTERIES

Max.Ws Out	1553W
Spindle Diameter	M14
Wheel Thickness	6 mm
Wheel Diameter	125 mm
Voltage	18V
No Load Speed	9000 rpm
Mode Select	2
Weight	1.75 kg

POWERSTACK TOOL KITS

18V XR SDS PLUS 2 X 5AH POWERSTACK

DCH273H2T

Voltage	18V
Impact Energy	2.1 Joule
Max Drilling Capacity	Wood 26 mm / Steel 13 mm / Masonry 24 mm
No Load Speed	0-1100 rpm
No Impact Rate	0-4600 ipm
Mode Select	3
Weight	3 kg

18V XR PREMIUM RECIP 2 X 5AH POWERSTACK

DCS386H2T

MaxWs Output	1475W
Max Cutting Capacity	PVC 160 mm / Wood 300 mm / Steel 130 mm
Voltage	18V
Strokes Per Min	0-3000 spm
Stroke Length	28.6 mm
Mode Select	3
Weight	3.5 kg

18V XR CIRC SAW 2 X 5AH POWERSTACK

DCS570H2T

Max. Torque	815W
Voltage	18V
No Load Speed	0-5200 rpm
Max Depth Of Cut	90º - 64 mm/ 45º - 48 mm
Blade Diameter	184 mm
Blade Bore	16 mm
Weight	3.6 kg

POWERSTACK TOOL KITS

Your DEWALT Dealer:

www.DEWALT.ae